

SZ998-038

In the Claims:

Please amend Claims 1-10 and 12-19 to read as follows:

B1

1. An apparatus for setting a transmission-rate parameter for transmission of information units in a wireless communication system, comprising:

- a total counter for counting a total number of received information units;
- an error counter for counting an error number of received invalid information units;
- a division unit for dividing said error number by said total number, the division result being providable as a link-quality measure at an output of said division unit; and
- a decision unit for automatically setting said transmission-rate parameter by comparing said link-quality measure with at least one predefined value and defining said transmission-rate parameter to assume a corresponding data rate.

2. Apparatus according to claim 1, wherein the link-quality measure or the transmission-rate parameter is sequentially updatable.

9.
3. An apparatus for setting a transmission-rate parameter for transmission of information units in a wireless communication system, comprising:

- a total counter for counting a total number of received information units;
- an error counter for counting an error number of received invalid information units;
- a division unit for dividing said error number by said total number, the division result being providable as a link-quality measure at an output of said division unit; and

SZ998-038

- a decision unit for setting said transmission-rate parameter by comparing said link-quality measure with at least one predefined value and defining said transmission-rate parameter to assume a corresponding data rate,
- wherein the link-quality measure is derivable iteratively increasing said total number after $2^n * f$ counted information units, with $n = 0, 1, 2, \dots$ and f a defined factor.

10. Apparatus according to claim ⁹~~8~~, wherein the division is executable at a multiple of factor f automatically by a shift operation corresponding to n .

3. Apparatus according to claim 1, wherein the error number is maintained between at least two subsequent updates of the link-quality measure.

B1 11. An apparatus for setting a transmission-rate parameter for transmission of information units in a wireless communication system, comprising:

- a total counter for counting a total number of received information units;
- an error counter for counting an error number of received invalid information units;
- a division unit for dividing said error number by said total number, the division result being providable as a link-quality measure at an output of said division unit; and
- a decision unit for setting said transmission-rate parameter by comparing said link-quality measure with at least one predefined value and defining said transmission-rate parameter to assume a corresponding data rate,

wherein the division unit comprises storage cells having a shift control, or comprises a multiplexer having a static logic.

SZ998-038

~~4.~~
~~7.~~ Apparatus of claim 1 further comprising a control unit which controls the total counter, the error counter, the division unit, and the decision unit.

~~5.~~
~~8.~~ Apparatus according to claim 1, wherein the division unit comprises the error counter.

~~6.~~
~~9.~~ Apparatus according to claim 1, wherein the decision unit comprises at least one comparator and a derivation unit for deriving from at least one output of said comparator the transmission-rate parameter.

~~11.~~
~~10.~~ Apparatus according to claim 1, wherein at least four predefined values are preloadable thresholds which correspond to a data rate of 4, 2, 1, 0.5 or 0.25 Mb/s, respectively.

~~8.~~
~~11.~~ An adaptive variable data-rate system for transmitting data over an infrared link comprising an apparatus according to claim 1.

SZ998-038

12. A method for setting a transmission-rate parameter for transmission of information units in a wireless communication system, comprising the steps of:

- counting a total number of received information units;
- counting an error number of received invalid information units;
- dividing said error number by said total number and providing the division result as a link-quality measure;
- comparing said link-quality measure with at least one predefined value; and
- automatically setting said transmission-rate parameter depending on the result of the comparison.

13. Method according to claim 12, wherein the link-quality measure or the transmission-rate parameter is sequentially updated.

18.
14. A method for setting a transmission-rate parameter for transmission of information units in a wireless communication system, comprising the steps of:

- counting a total number of received information units;
- counting an error number of received invalid information units;
- dividing said error number by said total number and providing the division result as a link-quality measure;
- comparing said link-quality measure with at least one predefined value; and
- setting said transmission-rate parameter depending on the result of the comparison, wherein the link-quality measure is derived after receiving a number of information units that is a multiple of 2^n , with $n = 0, 1, 2, \dots$.